

FloWise® Pro Series Quick Disconnect Control Box

With features you have come to expect in the industry, the new CBFP FloWise® Pro Series Control Box is designed and built to meet contractor's demanding standards. The heavy-duty construction, Voltage Relay and Resistor equipped Capacitors makes our Control Box dependable and the universal Quick Disconnect design makes installation quick and easy.

Features:

- Heavy Gauge Steel Enclosure rated for Indoor/Outdoor Use, Nema 3R
- Contractor Preferred Voltage Relay
- Resistor Equipped Capacitors to help protect against electrical shock
- Tested and Reliable Components
- Universal Design Allows for Easy Disconnect/Reconnect of Cover
- Ample room for easy Installation of After Market Protection Devices
- Two grounding lugs
- Seven Wiring Knockouts

CONTROL BOX SPECIFICATIONS									
MODEL	НР	VOLTS	РН	HZ	STD. CIRCUIT BREAKER AMPS	STD. FUSE	DUAL ELEMENT TIME DELAY FUSE	CAPACITOR	VOLTAGE RELAY
CBFP5-1	1/2	115V	1	60	30A	35A	20A	250-300MFD, 115V	115V
CBFP5-2	1/2	230V	1	60	15A	20A	10A	59-71MFD, 230V	230V
CBFP7-2	3/4	230V	1	60	20A	25A	15A	86-103MFD, 230V	230V
CBFP10-2	1	230V	1	60	25A	30A	20A	105-126MFD, 230V	230V





